

**Amendment and Response**

Page 2 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

**Amendments to the Claims**

This listing of claims replaces all prior versions, and listings, of claims in the above-identified application:

17. (Previously Presented) A production tool for manufacturing an abrasive article that comprises a major surface having deployed in fixed position thereon first and second three-dimensional abrasive composites, each of said composites comprising abrasive particles dispersed in a binder and having a shape defined by a substantially distinct and discernible boundary which includes substantially specific dimensions, wherein said first abrasive composite has a shape having specific first dimensions and said second abrasive composite has a second shape having second specific dimensions, wherein each of said abrasive composites has a boundary defined by at least four planar surfaces, wherein adjacent planar surfaces of one composite meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first abrasive composite is different from all of the angles of intersection of said second composite, said production tool comprising a structure having a plurality of adjacent three-dimensional cavities formed on a major surface thereof, wherein each three-dimensional cavity is defined by a substantially distinct and discernible boundary which includes substantially specific dimensions, wherein a first three-dimensional cavity has a first shape having specific first dimensions and a second three-dimensional cavity has a second shape having second specific dimensions, wherein each of said three-dimensional cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one three-dimensional cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first three-dimensional cavity is different from all angles of intersection of said second three-dimensional cavity, wherein said three-dimensional cavities comprise pyramidal shapes, wherein each pyramidal shape comprises planar surfaces which intersect to form a material-included angle at a distal end of said pyramid, wherein

**Amendment and Response**

Page 3 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

said material-included angle is a value from 25° to 90°, and wherein each of the cavities has a single opening.

19. (Previously Presented) A production tool useful to shape an abrasive slurry into an array of three-dimensional nonidentical abrasive composites, said production tool manufactured by a method comprising:

(A) preparing a master tool, the method comprising:

(1) determining angles corresponding to facing right and left planar surfaces of adjacent three-dimensional shapes and wherein each of said angles has a value as measured between its planar surface and a plane which extends in a normal direction to said major surface and contains an edge of said planar surface in contact with said major surface, by the following substeps:

(i) selecting an angle value between, but not including, 0° and 90° to establish a first right half angle of a first right planar surface of a first right-side three-dimensional shape with a random number generating means capable of randomly selecting an angle value between, but not including, 0° and 90°;

(ii) selecting an angle value between, but not including, 0° and 90° with said random number generating means to establish a first left half angle for a first left planar surface of a first left-side three-dimensional shape facing said first right planar surface of said first right-side three-dimensional shape;

(iii) proceeding along a first direction extending linearly within said first imaginary plane to a second left planar surface of a second left-side three-dimensional shape located adjacent said first left-side three-dimensional shape and using said random number generating means to select a value between, but not including, 0° and 90° to establish a second left planar angle for said second left planar surface;

(iv) using said random number generating means to select a value between, but not including, 0° and 90° for a second right planar surface of a second right-side three-

**Amendment and Response**

Page 4 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

dimensional shape facing said second left planar surface;

(v) proceeding along said first direction to a third right-side three-dimensional shape located adjacent said second right-side three-dimensional shape;

(vi) repeating said substeps (i), (ii), (iii), (iv), and (v), in that sequence, at least once;

(2) repeating step (1) except that the angles are determined for left and right planar surfaces of adjacent three-dimensional shapes deployed in two adjacent rows in a second direction extending linearly within said first imaginary plane, wherein said first and second directions intersect;

(3) using means to determine, for a given width of said surface of said master tool, locations of grooves required to be cut by a cutting means to form a series of intersecting grooves defining a plurality of three-dimensional shapes having said angles calculated by steps (1) and (2); and

(4) providing a cutting means to cut grooves in said surface of said master tool in correspondence to said angles calculated by steps (1) and (2) and said groove locations determined by step (3) to form a series of intersecting grooves which define a plurality of three-dimensional shapes upraised from said surface, each of said shapes being defined by a distinct and discernible boundary including specific dimensions, wherein not all said three-dimensional shapes are identical; and

(B) forming the production tool using the master tool.

20. (Previously Presented) A production tool for manufacturing an abrasive article that comprises a major surface having deployed in fixed position thereon first and second three-dimensional abrasive composites, each of said composites comprising abrasive particles dispersed in a binder and having a shape defined by a substantially distinct and discernible boundary which includes substantially specific dimensions, wherein said first abrasive composite has a shape having specific first dimensions and said second abrasive composite has a second shape having second specific

**Amendment and Response**

Page 5 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

dimensions, wherein each of said abrasive composites has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one composite meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first abrasive composite is different from all of the angles of intersection of said second composite, said production tool comprising a structure having a plurality of adjacent three-dimensional cavities formed on a major surface thereof, wherein each three-dimensional cavity is defined by a substantially distinct and discernible boundary which includes substantially specific dimensions, wherein a first three-dimensional cavity has a first shape having specific first dimensions and a second three-dimensional cavity has a second shape having second specific dimensions, wherein each of said three-dimensional cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one three-dimensional cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first three-dimensional cavity is different from all angles of intersection of said second three-dimensional cavity, wherein the production tool is a roll, and wherein each of the cavities has a single opening.

21. (Previously Presented) A production tool for manufacturing an abrasive article that comprises a major surface having deployed in fixed position thereon first and second three-dimensional abrasive composites, each of said composites comprising abrasive particles dispersed in a binder and having a shape defined by a substantially distinct and discernible boundary which includes substantially specific dimensions, wherein said first abrasive composite has a shape having specific first dimensions and said second abrasive composite has a second shape having second specific dimensions, wherein each of said abrasive composites has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one composite meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first abrasive composite is different from all of the angles of intersection of said second composite, said production tool comprising a structure having a plurality of adjacent three-dimensional cavities formed on a major surface thereof, wherein each three-dimensional cavity is defined by a substantially distinct and

**Amendment and Response**

Page 6 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

discernible boundary which includes substantially specific dimensions, wherein a first three-dimensional cavity has a first shape having specific first dimensions and a second three-dimensional cavity has a second shape having second specific dimensions, wherein each of said three-dimensional cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one three-dimensional cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first three-dimensional cavity is different from all angles of intersection of said second three-dimensional cavity, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

25. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, and wherein each of the cavities has a single opening.

26. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 30% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, and wherein each of the cavities has a single opening.

27. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 50% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, and wherein each of the cavities has a single opening.

28. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have a geometric shape, dimensions defining the cavity, and angles forming the geometric shape, wherein the angles are different in at

**Amendment and Response**

Page 7 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

least two of the cavities, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, and wherein each of the cavities has a single opening.

33. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape and the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second plurality of angles, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

34. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, and the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second and third plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first and third plurality of angles, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

35. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles

**Amendment and Response**

Page 8 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

forming the geometric shape, the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape and fourth plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second, third, and fourth plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first, third, and fourth plurality of angles, wherein at least one of the angles of the third plurality is different from all of the angles of the first, second, and fourth plurality of angles, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

36. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

37. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 30% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

38. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 50% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

**Amendment and Response**

Page 9 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

39. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have a geometric shape, dimensions defining the cavity, and angles forming the geometric shape, wherein the angles are different in at least two of the cavities, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

40. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least two adjacent cavities have at least one dimension different between the two cavities, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

41. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of cavities has a first shape and a second group of cavities has a second, different, shape, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

42. (Currently Amended) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of cavities has a first size and a second group of cavities has a second, different[[,]] size, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

43. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defined by substantially distinct and discernible boundaries which include substantially specific dimensions, wherein a first cavity has specific first dimensions and a second cavity has specific second dimensions, each of said cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one cavity meet at an edge to define an angle



**Amendment and Response**

Page 10 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

of intersection therebetween, wherein at least one angle of intersection of said first cavity is different from all the angles of intersection of said second cavity, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

44. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape and the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second plurality of angles, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

45. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, and the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second and third plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first and third plurality of angles, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

46. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles

**Amendment and Response**

Page 11 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

forming the geometric shape, the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape and fourth plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second, third, and fourth plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first, third, and fourth plurality of angles, wherein at least one of the angles of the third plurality is different from all of the angles of the first, second, and fourth plurality of angles, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

47. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

48. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 30% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

49. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 50% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

**Amendment and Response**

Page 12 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

50. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have a geometric shape, dimensions defining the cavity, and angles forming the geometric shape, wherein the angles are different in at least two of the cavities, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

51. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least two adjacent cavities have at least one dimension different between the two cavities, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

52. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of cavities has a first shape and a second group of cavities has a second, different, shape, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

53. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of cavities has a first size and a second group of cavities has a second, different, size, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

54. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defined by substantially distinct and discernible boundaries which include substantially specific dimensions, wherein a first cavity has specific first dimensions and a

**Amendment and Response**

Page 13 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

second cavity has specific second dimensions, wherein each of said cavities has a boundary defined by at least four planar surfaces, wherein adjacent planar surfaces of one cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first cavity is different from all the angles of intersection of said second cavity, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

94. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 10% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, and wherein each of the cavities has a single opening.

95. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 30% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, and wherein each of the cavities has a single opening.

96. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 50% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, and wherein each of the cavities has a single opening.

98. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the

**Amendment and Response**

Page 14 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

geometric shape and the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second plurality of base edge lengths, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

99. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, and the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second and third plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first and third plurality of base edge lengths, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

100. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape including a base and fourth plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is

**Amendment and Response**

Page 15 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

different from all of the base edge lengths of the second, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the third plurality is different from all of the base edge lengths of the first, second, and fourth plurality of base edge lengths, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

101. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 10% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

102. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 30% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

103. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 50% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

104. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the

**Amendment and Response**

Page 16 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

dimensions including base edge lengths, wherein at least two adjacent cavities have at least one base edge length different between the two cavities, wherein the production tool is a coating roll, and wherein each of the cavities has a single opening.

105. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape and the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second plurality of base edge lengths, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

106. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, and the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second and third plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first and third plurality of base edge lengths, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

**Amendment and Response**

Page 17 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

---

107. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape including a base and fourth plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the third plurality is different from all of the base edge lengths of the first, second, and fourth plurality of base edge lengths, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

108. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 10% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

109. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 30% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.



**Amendment and Response**

Page 18 of 25

Serial No.: 09/520,032

Confirmation No.: 9385

Filed: 6 March 2000

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

110. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 50% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.

111. (Previously Presented) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least two adjacent cavities have at least one base edge length different between the two cavities, wherein the production tool is an engraved metal roll, and wherein each of the cavities has a single opening.